




ALUMINIOS Perfiles Normalizados



Ángulos de lados desiguales

Dimensiones (mm)			Peso (Kg/ml)	MLX (cm)	MLY (cm)	WX (cm)	WY (cm)
b	h	e					
20	10	1,5					
25	10	2	1,188	0,043	0,422	0,053	0,274
30	15	1,5	0,188	0,114	0,625	0,095	0,322
30	15	2	0,233	0,135	0,489	0,119	0,299
30	20	2	0,260	0,325	0,894	0,214	0,444
30	25	6	0,835	1,490	2,390	0,870	1,220
35	15	1,5	0,210	0,116	0,952	0,091	0,426
40	20	2	0,331	0,351	1,967	0,221	0,760
40	25	2	0,341	0,664	2,126	0,343	0,791
40	30	2	0,369	1,112	2,256	0,487	0,815
50	15	2	0,355	0,153	3,270	0,122	1,091
50	25	2	0,416	0,700	3,901	0,345	1,195
60	15	2	0,416	0,163	5,396	0,125	1,532
60	32	2	0,508	1,475	6,963	0,573	1,753
60	40	2	0,553	2,775	7,513	0,888	1,819
60	40	4	1,088	5,183	14,272	1,704	3,521
65	30	6	1,510	3,171	22,924	1,381	5,663
70	35	2	0,588	1,974	10,901	0,695	2,374
70	35	3	0,865	2,851	15,972	1,014	3,508
70	50	5	1,703	12,660	34,850	3,320	6,884
80	20	2	0,555	0,395	13,000	0,230	2,753
80	40	2	0,664	2,984	16,370	0,914	3,110
85	25	1,7	0,524	0,665	14,091	0,309	2,735
100	50	6	2,450	15,895	90,575	4,035	14,076
100	75	9,5	4,459	75,830	156,622	13,683	23,068
103	36	2	0,774	0,231	31,249	0,755	4,879
110	70	8	3,905	55,214	171,501	10,347	23,376
150	90	9,5	6,204	143,144	513,367	20,584	51,575
180	70	10	6,808	74,627	811,627	13,265	72,957
200	100	9,52	7,844	208,470	1173,265	26,170	90,487

Nota: longitud de suministro 6.000 mm, bajo pedido cualquier otra longitud.